

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **64-086778**
 (43)Date of publication of application : **31.03.1989**

(51)Int.Cl.

H04N 7/08(21)Application number : **62-245167**(71)Applicant : **MATSUSHITA ELECTRIC IND CO LTD**(22)Date of filing : **29.09.1987**(72)Inventor : **UNEMURA TOYOAKI
ISHIDA MAKOTO
ISHIBASHI YOICHI
SHINPO HIROYASU
TAKADA YUKIO
KONDO TOMOJI
HENMI HIDEMI
FUKUDA CHIKA
SAKAMOTO MASARU**

(54) TELETEXT RECEIVER

(57)Abstract:

PURPOSE: To immediately display a title broadcast on a display by connecting between a television control part and a TELETEXT decoder part by a bus line, discriminating a title code by a title detection part in the television control part, synchronizing an output signal with a television signal, and setting a mode at a superimpose mode.

CONSTITUTION: The bus line connects between the television control part 5 and a TELETEXT control part 6. Here, by depressing a title key at the input part 4 of a remote control transmitter, etc., the title detecting part 9 in the television control part 5 detects the fact, and sends detected output and its title code to the part 6. The part 6 receiving the detected output and the title code starts an operation immediately, and samples a TELETEXT signal from a video signal, and also, detects the title code from a buffer RAM. And when a requested title exists, title data is written on a VRAM7. The title data written on the VRAM is read out synchronizing with the television signal, and is converted to an R, a G, and a B signals, and outputted to a video synthesis part 3.

